SYLVANIA



Concord

Beacon Introduction

The Concord Beacon range of spotlights is one of the most comprehensive on the market, offering both new cutting-edge LED technology and a wide selection of traditional lamp sources, providing complete versatility for display and accent lighting applications. Beacon introduces a timeless but contemporary all die-cast aluminium design based around simple geometric shapes offering a selection of beam angles and additional filters and accessories to complete the range.

The Beacon LED spotlight and BRA introduce a new lighting dimension to retail and display spaces, both ranges meet the tough demands of these environments by providing good colour rendering, zero UV/IR radiation, reduction in maintenance costs and an energy saving solution over existing lamp sources such as low voltage halogen.

Beacon High Output introduces a new concept in reflector design using 99.98% super pure aluminium material which introduces a high output, super efficient spotlight range for 20, 35W & 70W CMI-T lamps. The high efficiency of the new optics used for both spot and flood versions means that it is possible to use lower wattage lamps and still achieve similar light intensity levels. Beacon HO provides the ultimate CMI-T energy saving solution for shop lighting applications.



Beacon Range overview

BRA CMI-Tmini/ CMH-Super Mini - Accessories

Beacon LED	BRA (Beacon Recessed Adjustable)	Beacon High Output	Beacon CMI/CDM-T	Beacon CMI/Tmini/ CMH-Super Mini	Beacon Low Energy TC/TEL	Beacon Low Voltage Capsule and Dichroic	Beacon Britespot	Beacon Mains Voltage
Page 08-13	Page 14-19	Page 20-23	Page 24-27	Page 28-31	Page 32-33	Page 34-38	Page 39	Page 40-42
Beacon LED - Spot	BRA LED - Spot	Beacon High Output 35 & 70w - Spot	Beacon CMI/CDM-T 35 & 70w - Spot	Beacon CMI-Tmini/ CMH-Super Mini 20 & 35w - Spot	Beacon Low Energy - 26/32/42wTC-TEL	Beacon Low Voltage 50w Capsule - Spot	Britespot 35W - Spot	Beacon Mains Voltage 100w Hi-Spot 95
Beacon LED Plus - Spot	BRA LED - Flood	Beacon High Output 35 & 70w - Flood	Beacon CMI/CDM-T 35 & 70w - Flood	Beacon CMI-Tmini/ CMH-Super Mini 20 & 35w - Flood		Beacon Low Voltage 50w Capsule - Flood		Beacon Mains Voltage 50w Hi-Spot ES50
Beacon LED - Flood	BRA CMI-Tmini/ CMH-Super Mini - Spot		Beacon CMI/CDM-T 35 & 70w - Accessories	Beacon CMI-Tmini/ CMH-Super Mini - Accessories		Beacon Low Voltage Dichroic 20 - 50w		
Beacon LED Plus - Flood	BRA CMI-Tmini/ CMH-Super Mini - Flood					Beacon Low Voltage 50w Capsule - Accessories		


4 SPOTLIGHTS 5 SPOTLIGHTS

Beacon LED Technology

Colour Temperature

Colour temperature is a characteristic of visible light that plays a significant role in lighting applications. The colour temperature of a light source is the temperature of a perfect black-body radiator that radiates light of a similar appearance to that of the light source. The colour temperature is measured in units of absolute temperature; Kelvin (K).

Colour temperature works paradoxically to our cultural associations with colour, red as hot and blue as cold. On the black-body curve, blue occurs at higher temperatures than red. A good example is a candle which has a warm red orange appearance but in fact has a low Kelvin temperature, 1850 K. Therefore higher colour temperatures (5000 K more) are called cool colours (blueish white); lower colour temperatures (2700 – 3000 K) are called warm colours (yellowish white through red).



The Planckian locus shows the chromaticities of blackbody light sources of various colour temperatures and lines of constant correlated colour temperature shown within the CIE chromaticity diagram.

Colour Correlated Temperature (CCT)

An incandescent light bulb is very close to a perfect black-body radiator, so its colour temperature is basically the temperature of the filament. However many light sources, such as fluorescent tubes or high intensity discharge lamps, emit light by processes other than thermal radiation and therefore it is not possible to apply the black-body spectrum. For these light sources it is possible to assign what is known as a colour correlated temperature (CCT). The CCT is the colour temperature of a black-body (Planckian) radiator which most closely matches the colour of the light emitted from the lamp.

Warm White 3000K




Neutral White 4000K

Colour Rendering Index (CRI)

The colour rendering of a light source is an indicator of its ability to realistically reproduce the colour of an object. The chart illustrates our ability to accurately determine colour depending on the colour rendering properties of the light source. The higher the colour rendering index (on a scale of 0 to 100) of the source the better our ability to perceive differences in colour, which is a considerable aid to highlighting fashion products and effective display of coloured artworks.

The CIE colour rendering index (CRI) is a method to determine how well a light source's illumination of eight standardised colour patches compares to the illumination provided by a reference source. At Ra (8) the perceived colour shift of eight reference colours is measured as a percentage and averaged to give one number. However it is currently understood that due to the spectral power distribution of LED's that instead of using the standard Ra8 it is important to include 7 additional colours which include red, yellow, blue & green and use Ra14 to ensure better results.

Typical application





Binning

The term binning refers to the variations which occur within a single production batch of LED's such as chromaticity, lumen output and forward voltage. It is important that a specific bin has been identified and selected to ensure a uniform and constantly even lighting installation is achieved. If all the LED's were selected from one production batch and used in the same luminaire or installation, there would be a mix of colour temperatures and brightness levels. For the lighting manufacturer / designer binning is an essential part of LED specification.

MacAdam ellipses methodology was created in 1943 for mathematically constructing ellipses around target points, something which became very useful for the lamp industry. ANSI C78.377 is now the standard for chromaticity specified by the American National Standards Institute. ANSI recommends that lamp manufacturers stay within a "4-step" ellipse. This means that, given a certain target point on the CIE diagram, manufacturers are given a fairly wide range of perceptible differences. The CITILED light engine products comply with the "3-step" MacAdam ellipses, meaning the chromaticity ranges are narrowed to approximately a ninth of the ANSI standard.

Lumen Maintenance

Rated Lumen Maintenance Life (Lxx): The elapsed operating time over which the LED light source will the percentage, xx, of its initial light output.

• L80 = Time to 80% lumen maintenance, in hours • L70 = Time to 70% lumen maintenance, in hours For LED lamps, lumen maintenance is often shown as curves of relative lumen output over time for the LED under various operating conditions, such as drive current and junction temperature.


Junction Temperature (Tj)

The temperature of the Junction of the LED die inside the LED lamp. Measuring the LED die temperature by direct mechanical means is difficult and may lead to erroneous results. It is recommended that the Tj is calculated with manufacturer's data through measurement of the temperature at the solder point (Tsp).


Product specification


Non Dim Forward Current	910mA
Total Circuit Power	20W
Dim Forward Current	700mA
Total Circuit Power	15W
Typical CRI 3000K	Ra 85
Typical CRI 4000K	Ra 85
Typical CRI 3000K Beacon LED Plus	Ra 92
Maximum Junction Temperature (Tj)	120°C
Maximum Temperature	
Solder Point (Tsp)	88°C
Beacon LED Non Dim 910mA Tsp	67°C
BRA LED Non Dim 910mA Tsp	76°C
Beacon LED Dim 700mA Tsp	53°C
BRA LED Dim 700mA Tsp	62°C


MacAdam ellipses 3 / 5 / 7 SDCM



Chromaticity range chart







6 SPOTLIGHTS 7 SPOTLIGHTS





Beacon LEDSpotlights

9 SPOTLIGHTS

Beacon LED – Spot



- New high output high efficiency LED spotlight range
 Contemporary, compact all die-cast design
 Cutting-edge cooling fin design to maximise thermal management and reduction of LED junction temperature
- IR/UV free light source without heat radiation
 Energy efficient light source with far superior luminous flux per watt than existing Low Voltage Halogen
 Long life up to 50K hours, fit and forget maintenance free
- lighting solution
- Dimmable versions with on board dimming from 100% 0% output
- Available in 15° spot or 30° flood options
- Choice of colour temperatures warm 3000K & neutral 4000K
- Beacon Plus version offers high CRI, typical Ra92 ideal for museums, galleries and high end shop lighting applications




Beacon LED spot comes complete with Light Spill Baffle


Beacon LED Spot	3000K	White	Silver	Black	
LED Spot	Single Circuit	2048776	2048777	2048778	0.85kg
LED Spot Dim	Single Circuit	2048807	2049457	2049458	0.85kg
LED Spot	Three Circuit	2048764	2048765	2048766	0.85kg
LED Spot Dim	Three Circuit	2048788	2048789	2048790	0.85kg
Beacon LED Spot	4000K	White	Silver	Black	
LED Spot	Single Circuit	2048779	2048780	2048781	0.85kg
LED Spot Dim	Single Circuit	2049459	2049460	2049461	0.85kg
LED Spot	Three Circuit	2048767	2048768	2048769	0.85kg
LED Spot Dim	Three Circuit	2048791	2048792	2048793	0.85kg

3020010 3020030

2049498







Monopoint For surface mounting on to ceiling and walls 3020060 3020070 Single Circuit

Accessories

Three Circuit

Beacon LED Coloured Gel Pack

10 SPOTLIGHTS 11 SPOTLIGHTS

Beacon LED Plus – Spot




- New high output high efficiency LED spotlight range
 Contemporary, compact all die-cast design
 Cutting-edge cooling fin design to maximise thermal management and reduction of LED junction temperature
- IR/UV free light source without heat radiation
- Energy efficient light source with far superior luminous flux per watt than existing Low Voltage Halogen
 Long life up to 50K hours, fit and forget maintenance free
- lighting solution
- Dimmable versions with on board dimming from 100% 0% output
- Available in 15° spot or 30° flood options
- Choice of colour temperatures warm 3000K & neutral 4000K
- Beacon Plus version offers high CRI, typical Ra92 ideal for museums, galleries and high end shop lighting applications



Beacon LED spot comes complete with Light Spill Baffle


Beacon LED Plus	Spot 3000K	White	Silver	Black		
LED Plus Spot LED Plus Spot	Single Circuit Three Circuit				0.85kg 0.85kg	





Citizen CITILED CL-L233

Luminous Flux 3000K 725 lm




Monopoint For surface mounting on to ceiling and walls

3020060 3020070 Single Circuit Three Circuit 3020010 3020030

Accessories

Beacon LED Coloured Gel Pack 2049498




Beacon LED - Flood




- New high output high efficiency LED spotlight range
 Contemporary, compact all die-cast design
 Cutting-edge cooling fin design to maximise thermal management and reduction of LED junction temperature
- IR/UV free light source without heat radiation
 Energy efficient light source with far superior luminous flux per watt than existing Low Voltage Halogen
 Long life up to 50K hours, fit and forget maintenance free
- lighting solution
- Dimmable versions with on board dimming from 100% 0% output
- Available in 15° spot or 30° flood options
- Choice of colour temperatures warm 3000K & neutral 4000K
- Beacon Plus version offers high CRI, typical Ra92 ideal for museums, galleries and high end shop lighting applications



Beacon LED Floor	3000K	White	Silver	Black	
LED Flood	Single Circuit	2048782	2048783	2048784	0.85kg
LED Flood Dim	Single Circuit	2049465	2049466	2049467	0.85kg
LED Flood	Three Circuit	2048770	2048771	2048772	0.85kg
LED Flood Dim	Three Circuit	2048797	2048798	2048799	0.85kg
Beacon LED Floor	d 4000K	White	Silver	Black	
LED Flood	Single Circuit	2048785	2048786	2048787	0.85kg
LED Flood Dim	Single Circuit	2049468	2049469	2049470	0.85kg
LED Flood	Three Circuit	2048773	2048774	2048775	0.85kg
LED Flood Dim	Three Circuit	2048801	2048802	2048803	0.85kg








Monopoint For surface mounting on to ceiling and walls 3020060 3020070 Single Circuit Three Circuit 3020010 3020030

Accessories

Beacon LED Coloured Gel Pack 2049498 Beacon Flood Lens (To give 40deg beam) 2049499



12 **SPOTLIGHTS** 13 SPOTLIGHTS


Beacon LED Plus - Flood



- New high output high efficiency LED spotlight range
 Contemporary, compact all die-cast design
 Cutting-edge cooling fin design to maximise thermal management and reduction of LED junction temperature
- IR/UV free light source without heat radiation
- Energy efficient light source with far superior luminous flux per watt than existing Low Voltage Halogen
 Long life up to 50K hours, fit and forget maintenance free
- lighting solution
- Dimmable versions with on board dimming from 100% 0% output
- Available in 15° spot or 30° flood options
- Choice of colour temperatures warm 3000K & neutral 4000K
- Beacon Plus version offers high CRI, typical Ra92 ideal for museums, galleries and high end shop lighting applications



Beacon LED Plus Spot 3000K White Single Circuit **2049471 2049472 2049473** 0.85kg LED Flood LED Flood Three Circuit **2048804 2048805 2048806** 0.85kg







Citizen CITILED CL-L233

Luminous Flux 3000K 725 lm

2049471






Monopoint For surface mounting on to ceiling and walls

3020060 3020070 Single Circuit Three Circuit 3020010 3020030

Accessories

Beacon LED Coloured Gel Pack 2049498 Beacon Flood Lens (To give 40deg beam) 2049499





BRA (Beacon Recessed Adjustable) LED Spot



- New high output high efficiency LED recessed adjustable fixtures
 IR/UV free light source without heat radiation
 Cutting-edge cooling fin design to maximise on thermal management and reduction of LED junction temperature
 Energy efficient light source with far superior luminous flux per watt than existing Low Voltage Halogen
 Long life up to 50K hours, fit and forget maintenance free lighting solution
- lighting solution
- lighting solution
 Dimmable options including phase dimming via leading or trailing edge dimmers or DALI as standard
 Choice of colour temperatures warm 3000K & neutral 4000K
 Available with either square or round mounting plates
 Offers complete flexibility with 35° tilt facility and 355° rotation
 Available in 15° spot or 30° flood options
 Ideal for accent lighting and shop lighting applications
 Luminaires supplied complete with LED drivers




BRA BRA LED White Spot BRA LED White Spot Dim BRA LED White Spot DALI	Trim Round Round Round	3000K 2049474 2049478 2050752	4000K 2049476 2049480 2050754	1.0kg 1.0kg 1.0kg
BRA LED White Spot BRA LED White Spot Dim BRA LED White Spot DALI	Square Square Square	2049482 2049486 2020756	2049484 2049488 2020758	1.0kg 1.0kg 1.0kg







15°

Luminous Flux 4000K 1055 lm Luminous Flux 3000K 960 lm




BRA (Beacon Recessed Adjustable)
Spotlights





14 **SPOTLIGHTS** 15 SPOTLIGHTS




- New high output high efficiency LED recessed adjustable fixtures
 IR/UV free light source without heat radiation
- Cutting-edge cooling fin design to maximise on thermal management and reduction of LED junction temperature
- Energy efficient light source with far superior luminous flux per watt than existing Low Voltage Halogen


 Long life up to 50K hours, fit and forget maintenance free
- lighting solution
- Dimmable options including phase dimming via leading or trailing edge dimmers or DALI as standard
- Choice of colour temperatures warm 3000K & neutral 4000K
- Available with either square or round mounting plates
 Offers complete flexibility with 35° tilt facility and 355° rotation
- Available in 15° spot or 30° flood options
- Ideal for accent lighting and shop lighting applications
 Luminaires supplied complete with LED drivers



RA	Trim	3000K	4000K	
RA LED White Flood	Round	2049475	2049477	1.0kg
RA LED White Flood Dim	Round	2049479	2049481	1.0kg
RA LED White Flood DALI	Round	2020753	2020755	1.0kg
RA LED White Flood	Square	2049483	2049485	1.0kg
RA LED White Flood Dim	Square	2049487	2049489	1.0kg
RA LED White Flood DALI	Square	2020757	2020759	1.0kg








Accessories

Beacon Flood Lens (To give 40deg beam)

2049499



BRA (Beacon Recessed Adjustable)




CMI-Tmini - Spot

- Compact high output recessed adjustable downlight
 20W & 35W CMI-Tmini / CMH Supermini lamp options
 Luminaires complete with compact lightweight electronic control gear


- Robust twist and lock GU6.5 lamp base
 Available with either square or circular mounting plates
 Offers complete flexibility with 35° tilt and 355° rotation
 Available in 10° spot or 30° flood options
- Ideal for accent lighting and shop lighting applications
- Order lamp separately





Beacon REC ADJ 20w CMI-Tmini / CMH - Supermini White Spot	Trim Round	2049490	1.0
Beacon REC ADJ 35w CMI-Tmini / CMH - Supermini White Spot	Trim Round	2049492	1.0
Beacon REC ADJ 20w CMI-Tmini / CMH - Supermini White Spot	Trim Square	2049494	1.0
Beacon REC ADJ 35w CMI-Tmini / CMH - Supermini White Spot	Trim Square	2049496	1.0



CMI-Tmini/CMH-Supermini 6.5 20/35w 20w = 1600 Im35w = 3300 Im







16 **SPOTLIGHTS** 17 SPOTLIGHTS

BRA (Beacon Recessed Adjustable)



CMI-Tmini - Flood


- Compact high output recessed adjustable downlight
 20W & 35W CMI-Tmini / CMH Supermini lamp options
 Luminaires complete with compact lightweight electronic
- Robust twist and lock GU6.5 lamp base
- Available with either square or circular mounting plates
 Offers complete flexibility with 35° tilt and 355° rotation
- Available in 10° spot or 30° flood options
- Ideal for accent lighting and shop lighting applications]
 Order lamp separately




Beacon REC ADJ 20w CMI-Tmini / CMH - Supermini White Flood	Trim Round	2049491	1.0kg
Beacon REC ADJ 35w CMI-Tmini / CMH - Supermini White Flood	Trim Round	2049493	1.0kg
Beacon REC ADJ 20w CMI-Tmini / CMH - Supermini White Flood	Trim Square	2049495	1.0kg
Beacon REC ADJ 35w CMI-Tmini / CMH - Supermini White Flood	Trim Square	2049497	1.0kg



CMI-Tmini/CMH-Supermini 6.5 20/35w $20w=1600\;lm$ 35w = 3300 lm





BRA (Beacon Recessed Adjustable) CMI-Tmini/CMH-Super Mini Accessories


Interchangeable Safety Lenses

Elongation Lens 2047193


Optional Filters

Honeycomb	Not to be used in combination with colour filters	2047194
UV	100% UVB/C and 70% UVA protection	2047195
Daylight	Converts 3000k to 6000k	2047196
Flesh Tone	Enhances the appearance of flesh tone, vegetables and meat	2047197
Mid Blue		2047198
Red		2047199
Amber		2047200

Interchangeable Safety Lenses



Optional Filters



18 **SPOTLIGHTS** 19 SPOTLIGHTS





Beacon High Output Spotlights


Beacon High Output Spot



- Contemporary all die-cast design and construction
 Beacon High Output introduces a new concept in reflector design using 99.98% super pure aluminium
- High output super efficient spotlight range for 20, 35 & 70W CMI-T lamps
 The highly efficient optics used for both spot and flood versions means it
- is possible to use lower wattage lamps and still achieve similar light intensity levels.
- Beacon HO provides the ultimate energy saving solution for shop lighting applications



20W Spot		L1	L3	
Beacon 20W CDM-T	White	2050701	2050698	1.42kg
Beacon 20W CDM-T	Silver	2050702	2050699	1.42kg
Beacon 20W CDM-T	Black	2050703	2050700	1.42kg





CMI/CDM-T


35W G12

35W = 3400 Im


CMI/CDM-T


70W = 6200 Im


70W G12




35W Spot		L1	L3	
Beacon 35W CDM-T	White	2050713	2050710	1.42kg
Beacon 35W CDM-T	Silver	2050714	2050711	1.42kg
Beacon 35W CDM-T	Black	2050715	2050712	1.42kg








70W Spot		L1	L3	
Beacon 70W CDM-T	White	2050725	2050722	1.42kg
Beacon 70W CDM-T	Silver	2050726	2050723	1.42kg
Beacon 70W CDM-T	Black	2050727	2050724	1.42kg





Monopoint

For surface mounting on to ceiling and walls

3020010 3020030 Three Circuit

Beacon High Output Flood



- Contemporary all die-cast design and construction
 Beacon High Output introduces a new concept in reflector design using 99.98% super pure aluminium
- High output super efficient spotlight range for 20, 35 & 70W CMI-T lamps
 The highly efficient optics used for both spot and flood versions means it
- is possible to use lower wattage lamps and still achieve similar light intensity levels.
- Beacon HO provides the ultimate energy saving solution for shop lighting applications




0W Flood		L1	L3	
Beacon 20W CDM-T	White	2050707	2050704	1.42kg
Beacon 20W CDM-T	Silver	2050708	2050705	1.42kg
Beacon 20W CDM-T	Black	2050709	2050706	1.42kg












35W Flood		L1	L3	
Beacon 35W CDM-T	White	2050719	2050716	1.42kg
Beacon 35W CDM-T	Silver	2050720	2050717	1.42kg
Beacon 35W CDM-T	Black	2050721	2050718	1.42kg








70W Flood		L1	L3		Т
Beacon 70W CDM-T	White	2050731	2050728	1.42kg	
Beacon 70W CDM-T	Silver	2050732	2050729	1.42kg	9
Beacon 70W CDM-T	Black	2050733	2050730	1.42kg	











Monopoint

For surface mounting on to ceiling and walls

3020010 3020030 Three Circuit

22 **SPOTLIGHTS** 23 SPOTLIGHTS





Beacon CMI/CDM-T 35 & 70w **Spotlights**


Beacon CMI/CDM-T 35 & 70w Spot




- Contemporary, all die-cast design
 Compact electronic control gear
 No back light, lamp is fully enclosed at rear
 Robust G12 base CMI/CDM-T ceramic metal halide capsule lamp
- Range of filters and honeycomb accessory to customise display or accent interiors
- Available complete with spot or flood safety lens
 Interchangeable safety lenses determine beam angle
- Order lamp separatelySafety lenses must be used




Beacon CMI/CDM-T 35w 35w HIT-CE with Single Circuit **2046412 2046413 2046414** 1.42kg spot safety lens 35w HIT-CE with Three Circuit **2046418 2046419 2046420** 1.42kg spot safety lens








Beacon CMI/CDM-T 70w 70w HIT-CE with Single Circuit **2046424 2046425 2046426** 1.42kg spot safety lens 70w HIT-CE with Three Circuit **2046430 2046431 2046432** 1.42kg spot safety lens






70w Spot





For surface mounting on to ceiling and walls

Three Circuit 3020010 3020030



24 **SPOTLIGHTS** 25 SPOTLIGHTS


Beacon CMI/CDM-T 35w & 70w Flood





- Contemporary, all die-cast design
- Compact electronic control gear
- No back light, lamp is fully enclosed at rear
- Robust G12 base CMI/CDM-T ceramic metal halide capsule lamp
- Range of filters and honeycomb accessory to customise display or accent interiors
- Available complete with spot or flood safety lens
 Interchangeable safety lenses determine beam angle
- Order lamp separately
- Safety lenses must be used




Beacon CMI/CDM	I-T 35w	White	Silver	Black	
35w HIT-CE with	Single Circuit	2046415	2046416	2046417	1.42kg
flood safety lens					
35w HIT-CE with	Three Circuit	2046421	2046422	2046423	1.42kg
flood safety lens					








Beacon CMI/CDM 70w HIT-CE with		White 2046427	Silver 2046428	Black 2046429	1.42kg
flood safety lens 70w HIT-CE with flood safety lens	Three Circuit	2046433	2046434	2046435	1.42kg








Monopoint

For surface mounting on to ceiling and walls

Three Circuit 3020010 3020030



26 SPOTLIGHTS 27 SPOTLIGHTS

Beacon CMI/CDM-T 35 & 70w Accessories


- Interchangeable safety lenses provide beam angles from 13-35°
 Elongation safety lens for highlighting sculptures, mannequins, logos and shelving
- Coloured filters for creating dramatic effects and highlighting displays
- Honeycomb filter for effective glare control

2032127

2032128 2027244

2027245

A combination of accessories can be fitted but must always include a safety lens next to the lamp



Enhances the appearance of flesh tone, vegetables & meat


Flesh Tone

Mid Blue

Red

Amber

Interchangeable Safety Lenses





Beacon CMI-Tmini/CMH-Super Mini Spot



20w GU6.5

20w = 1615 lm

CMI-Tmini/CMH Sup


- Versatile slim minimalist, all die cast design
 Powerful display spotlight with a choice of 10° spot or 30° flood
 Compact lightweight integral electronic ballast
 No back light, lamp is fully enclosed at rear
 Robust twist and lock GU6.5 lamp base


- Accessories include a honeycomb, elongation, coloured, UV and daylight filters
 Order lamp separately



Beacon CMI-Tmini/CMH-Supermini 20w


White Three Circuit **2046670 2046671 2046672** 0.90kg 20w10° Spot Single Circuit **2046673 2046674 2046675** 0.90kg 20w 10° Spot






Beacon CMI-Tmini/CMH-Supermini 35w

35w 10° Spot Three Circuit **2046682 2046683 2046684** 0.90kg 35w 10° Spot Single Circuit **2046685 2046686 2046687** 0.90kg



CMI-Tmini/CMH Superi **35w** GU6.5 35w = 3300 Im





Monopoint For surface mounting on to ceiling and walls Single Circuit 3020060 3020070 Three Circuit 3020010 3020030

CMH-Super MiniSpotlights

28 SPOTLIGHTS 29 SPOTLIGHTS

Beacon CMI-Tmini/

Beacon CMI-Tmini/CMH-Super Mini Flood




- Versatile slim minimalist, all die cast design
 Powerful display spotlight with a choice of 10° spot or 30° flood
- Compact lightweight integral electronic ballast
- No back light, lamp is fully enclosed at rear
- Robust twist and lock GU6.5 lamp base
- Accessories include a honeycomb, elongation, coloured, UV and daylight filters
 Order lamp separately




Beacon	CMI-Tmini/CMH-Supermini 20w	

20w 30° Flood Three Circuit **2046676 2046677 2046678** 0.90kg Single Circuit **2046679 2046680 2046681** 0.90kg 20w 30° Flood




20w 30° Flood



Beacon CMI-Tmini/CMH-Supermini 35w


White 35w 30° Flood Three Circuit **2046688 2046689 2046690** 0.90kg 35w 30° Flood Single Circuit **2046691 2046692 2046693** 0.90kg




CMI-Tmini/CMH Superm

35w GU6.5 35w = 3300 Im

35w 30° Flood



Monopoint For surface mounting on to ceiling and walls Single Circuit 3020060 3020070 Three Circuit 3020010 3020030



Beacon CMI-Tmini/CMH-Super Mini Accessories


Interchangeable Safety Lenses

Elongation Lens 2047193


Optional Filters

Honeycomb	Not to be used in combination with colour filters	2047194
UV	100% UVB/C and 70% UVA protection	2047195
Daylight	Converts 3000k to 6000k	2047196
Flesh Tone	Enhances the appearance of flesh tone, vegetables and meat	2047197
Mid Blue		2047198
Red		2047199
Amber		2047200

Interchangeable Safety Lenses



Optional Filters



30 SPOTLIGHTS 31 SPOTLIGHTS



Beacon Low Energy 26/32/42w TC-TEL



Lynx-TE TC-TEL

26/32/42w XXX 26w = 1800 lm 32w = 2400 lm


42w = 3200 lm


- Contemporary design, die cast and spun aluminium
 A low energy spotlight with highly reflective, iridescence-free reflector
 Glare-free from most viewing angles giving an even soft edged beam
 Compact fluorescent lamp options, energy efficient
 Long lamp life reducing running and maintenance costs
 Supplied complete with Sylvania Lynx-TE 32w 840 4000K lamp



con TC/TE		White	Silver
2/42w Lynx-TEL	Single Circuit	2046711	2046712
2/42w Lvnx-TFI	Three Circuit	2046707	2046709

Accessories Black Glare Cowl 2047189





Monopoint For surface mounting on to ceiling and walls
Single Circuit 3020060 3020070 Single Circuit
Three Circuit 3020010 3020030

Beacon Low Energy TC/TEL **Spotlights**

32 **SPOTLIGHTS** 33 SPOTLIGHTS



Beacon Low Voltage 50w Capsule Spot



QT 12-LPax

50w GY6.35

50w = 1000 lm


- Versatile slim minimalist, all die-cast design
 Available as a 10° spot or a 30° flood
- Compact integral, voltage regulated electronic transformer
- Collectively dimmable using leading and trailing edge dimming systems
 No back light, lamp is fully enclosed at rear


- No back light, family is fully enclosed at real
 Accepts up to 50w low voltage TH capsule lamps
 Accessories include a honeycomb, elongation, coloured, UV and daylight filters
 Supplied complete with Sylvania 12v 50w low pressure TH lamp



Beacon Low Voltage 50w Capsule

50w TH 10° Spot Single Circuit **2046697 2046698 2046699** 0.70kg 50w TH 10° Spot Three Circuit **2046694 2046695 2046696** 0.70kg





Monopoint For surface mounting on to ceiling and walls

3020060 3020070 Single Circuit 3020010 3020030 Three Circuit

34 **SPOTLIGHTS** 35 SPOTLIGHTS

Beacon Low Voltage Capsule and Dichroic Spotlights




- Versatile slim minimalist, all die-cast design
- Available as a 10° spot or a 30° flood
- Compact integral, voltage regulated electronic transformer
- Collectively dimmable using leading and trailing edge dimming systems
- No back light, lamp is fully enclosed at rear
- Accepts up to 50w low voltage TH capsule lamps
- Accessories include a honeycomb, elongation, coloured, UV and daylight filters
- Supplied complete with Sylvania 12v 50w low pressure TH lamp




Beacon Low Voltage 50w Capsule

Black 50w TH 30° Flood Single Circuit **2046704 2046705 2046706** 0.70kg 50w TH 30° Flood Three Circuit **2046701 2046702 2046703** 0.70kg




50w 30° Flood



Monopoint For surface mounting on to ceiling and walls

3020060 3020070 Single Circuit 3020010 3020030 Three Circuit



36 **SPOTLIGHTS** 37 SPOTLIGHTS

Beacon CMI-Tmini/CMH-Supermini & Low Voltage 50w Capsule

Accessories


- Elongation safety lens for highlighting sculptures, mannequins, logos and shelving
 Coloured filters for creating dramatic effects and highlighting displays
- Honeycomb filter, screw-fit glare shield and barn door accessories for
- effective glare control
- A combination of accessories can be fitted but must always include a safety lens next to the lamp

Interchangeable Safety Lenses 2047193 5:1 Elongation Lens

Optional Filters UV

Honeycomb Not to be used in combination with colour filters 100% UVB/C and 70% UVA protection 2047195 2047196 Daylight Converts 3000k to 6000k Flesh Tone Enhances the appearance of flesh tone, vegetables and meat 2047197 Mid Blue 2047198 Red 2047199 Amber 2047200





Beacon Low Voltage




- Slim minimalist, all die-cast design
- Compact electronic transformer
- No back light, lamp is fully enclosed at rear
- 20 50w dichroic lamps
- Collectively dimmable using trailing and leading edge dimming systems
- Order lamp separately




Beacon Hi Spot ES50 50w QR-CBC51 Single Circuit **2041897 2041898 2041899** 0.58kg

50w QR-CBC51 Three Circuit **2041900 2041901 2041902** 0.58kg







50w 38° Flood


Monopoint For surface mounting on to ceiling and walls

3020060 3020070 Single Circuit Three Circuit 3020010 3020030

Accessories

Chrome Cowl/Ring

2045808



Beacon BriteSpot ES50 Metal Halide



35w GX10 35w = 3269 lm

BriteSpot ES50 HIPAR51


- Slim minimalist, all die-cast design
- Compact electronic control gear
- No back light, lamp is fully enclosed at rear
- Quartz metal halide reflector lamp technology from Sylvania
- Robust GX10 lamp base for easy lamp replacement
- Excellent colour rendering
- Twice the output of a 50w dichroic lamp
- Order lamp separately




Beacon Britespot ES50 35w HI-Par51 Single Circuit **2041903 2041904 2041905** 0.72kg 35w HI-par51 Three Circuit **2041906 2041907 2041908** 0.72kg

3020010 3020030

2045807



DLOR = 0.64






Optional Chrome Cowl

Monopoint For surface mounting on to ceiling and walls 3020060 3020070 Single Circuit

Accessories

Three Circuit

Chrome Cowl/Ring



38 SPOTLIGHTS 39 SPOTLIGHTS




Beacon 100w Hi-Spot 95




- Contemporary, all die-cast design
 Crisp halogen light without the need for transformer
 No back light, lamp is fully enclosed at rear
 Simple E27 lamp base allow easy lamp replacement
 Energy saving solutions with Sylvania retrofit PAR30 E27 LED HI-SPOT RefLED lamps
 Order lamp separately



Beacon Hi Spot 95		White	Silver	Black	
00w QPar30 Sir	ngle Circuit	2041891	2041892	2041893	0.59kg
00w QPar30 Th	ree Circuit	2041894	2041895	2041896	0.59kg



Monopoint For surface mounting on to ceiling and walls
Single Circuit 3020060 3020070 Single Circuit Three Circuit 3020010 3020030



40 **SPOTLIGHTS** 41 SPOTLIGHTS

Beacon Mains VoltageSpotlights

Beacon – Mains voltage 50w Hi-Spot ES50




- Slim minimalist, all die-cast design
 Crisp halogen light without the need for transformer
 No back light, lamp is fully enclosed at rear
 Robust GU10 lamp base for easy lamp replacement
 Energy saving solutions with Sylvania retrofit ES50 GU10 LED HI-SPOT RefLED lamps
 Order lamp separately



 Beacon Hi Spot ES50
 White
 Silver
 Black


 50w QPar16
 Single Circuit
 2041879
 2041880
 2041881
 0.41kg
 50w QPar16 Three Circuit **2041882 2041883 2041884** 0.41kg



Hi-Spot ES50 QPAR16 **50w** GU10 50W = 525 lm



Monopoint For surface mounting on to ceiling and walls Single Circuit 3020060 3020070 Three Circuit 3020010 3020030



EUROPE

Austria

info.be@havells-sylvania.com

Bulgaria, Romania and Macedonia Sofia

T. +359 885 971 285 F. +359 2 981 34 92

Czech Republic and Slovakia

T. +420 545 231 345 F. +420 545 231 346 info.cz@havells-sylvania.com

Eastern Europe

Erlangen T. +49 (0)9131 793 499 F. +49 (0)9131 793 496 info.de@havells-sylvania.com

Finland

T. +358 (0)9 5421 2100 F. +358 (0)9 5421 2130

France

T. +33 (0)1 55 51 11 00 F. +33 (0)1 55 51 11 15 info.fr@havells-sylvania.com

Germany

Erlangen T. +49 (0)9131 793 0 F. +49 (0)9131 793 345

Greece

Athens T. +30 210 996 65 61 F. +30 210 996 90 29 info.gr@havells-sylvania.com

Hungary

Budapest T. +36 (30) 50 69 182 F. +36 (24) 423 563 info.hu@havells-svlvania.com

Italy Milan

T. +39 02 24 12 58 11 F. +39 02 24 12 58 80 info.it@havells-sylvania.com

Netherlands

T. +31 (0)76 750 44 44 info.nl@havells-sylvania.com

Norway

F. +47 23 067471

Poland

F. +48 61 8720 413

Portugal

info.pt@havells-sylvania.com

Russia

info.ru@havells-sylvania.com

South East Europe Serbia, Croatia, Slovenia, Albania, Montenegro, Bosnia

and Herzegovina

Belgrade T. +381 (0)63 617 716

T. +34 91 669 90 00

Sweden

F. +46 8 556 322 10 info.se@havells-sylvania.com

Switzerland

F. +41 44305 31 81 info.ch@havells-sylvania.com

Turkey Istanbul T. +90 533 433 86 78 F. +90 212 343 46 10

UK

Newhaven

T. +44 (0)870 606 2030 F. +44 (0)1273 512 688 info.concord@ havells-sylvania.com

MIDDLE EAST

United Arab Emirates

ASIA

China

Guangzhou T. +86 20 3815 1138 F. +86 20 3869 7572 info.cn@havells-sylvania.com

marketing@havells.com

Kuala Lumpur T. +603 2031 8788 E +603 2031 4788

Thailand

info.th@havells-svlvania.com

Vietnam

T. +844 37 151 604 F. +844 37 151 605 info.vn@havells-sylvania.com

AMERICAS

Argentina

Buenos Aires T. +54 11 4515 0215 F. +54 11 4515 0215

Brazil

Caribbean Honduras, Nicaragua

T. +506 22 107 678 F. +506 22 328 723 info.cr@havells-sylvania.com

Colombia

Santafé de Bogota T. +57 1 782 5200 F. +57 1 719 9621

Costa Rica

San José T. +506 22 107 678 F. +506 22 200 338

Quito T. +593 2 328 4407

El Salvador

San Salvador T. +503 2239 2239 F. +503 2284 9670 info.sv@havells-sylvania.com

Guatemala

Guatemala City T. +502 2387 5300 F. +502 2387 5301

Mexico Mexico D.F. T. +52 55 5387 7670

Panama

F. +507 236 1315 info.pa@havells-sylvania.com

F. +1 843 464 2898

Venezuela

info.ve@havells-sylvania.com

www.concord-lighting.com